



SITE PHOTOMETRY  
NOT TO SCALE

### SITE LIGHTING NOTES

A. MOUNTING HEIGHT OF WALL PACK FIXTURE TO BE 11'-0" ABOVE FINISH GRADE.

B. AREA WALL PACK LIGHTING. CONTROL PER ASHRAE 90.1-2019: CONNECT TO PHOTOCELL VIA LIGHTING CONTROL PANEL, "LP". THE LIGHT SHOULD BE REDUCED BY 50% FROM MIDNIGHT TO 6 AM. COORDINATE EXACT LOCATION AND ALL REQUIREMENTS WITH OWNER AND SIGNAGE CONTRACTOR.

### WDGE3 LED Architectural Wall Sconce

**Specifications**

Depth (D1): 8"  
Depth (D2): 1.5"  
Height: 9"  
Width: 18"  
Weight: 19.5 lbs  
(Certified optional)

**Introduction**

The WDGE3 LED family is designed to meet specifier's every wall-mounted lighting need in a highly accented design that blends with any architecture. The clean rectangular design comes in four sizes with lumens packages ranging from 1,200 to 25,000 lumens, providing a true site-wide solution. Embedded with a light AIB sensor, the WDGE3 family provides additional energy savings and code compliance.

WDGE3 has been designed to deliver up to 12,000 lumens through a precision reflective lens with wide distribution, perfect for augmenting the lighting from pole-mounted luminaires.

### WDGE3 LED Family Overview

Series	Type	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)	Standard Lumens (4000K, 70CRI)
WDGE3 LED	Wall Sconce	1200	1800	2400	3000	3600	4200	4800	5400
WDGE3 LED	Wall Sconce	1200	1800	2400	3000	3600	4200	4800	5400
WDGE3 LED	Wall Sconce	1200	1800	2400	3000	3600	4200	4800	5400
WDGE3 LED	Wall Sconce	1200	1800	2400	3000	3600	4200	4800	5400

**Ordering Information**

EXAMPLE: WDGE3 LED P3 40K 70CRI R3 30VOLT SRM DBBXD

Series	Package	Color Temperature	CR	Beam Spread	Mounting	Shipped Included	Shipped Capacity
WDGE3 LED	P1	40K	70CRI	R3	30V	SRM	30V
P2	40K	70CRI	R3	30V	SRM	30V	
P3	40K	70CRI	R3	30V	SRM	30V	
P4	40K	70CRI	R3	30V	SRM	30V	

**Accessories**

WDGE3 LED: 18" x 9" x 8" (457mm x 229mm x 203mm) - 19.5 lbs (8.8 kg)

WDGE3 LED: 18" x 9" x 8" (457mm x 229mm x 203mm) - 19.5 lbs (8.8 kg)

WDGE3 LED: 18" x 9" x 8" (457mm x 229mm x 203mm) - 19.5 lbs (8.8 kg)

WDGE3 LED: 18" x 9" x 8" (457mm x 229mm x 203mm) - 19.5 lbs (8.8 kg)

Schedule									
Symbol	Label	QTY	Manufacturer	Catalog	Description	Number Lamps	Lamp Output	LLF	Input Power
	W1	7	Lithonia Lighting	WDGE3 LED P1 70CRI RFT 40K	WDGE3 LED WITH P1 - PERFORMANCE PACKAGE, 4000K, 70CRI, FORWARD THROW OPTIC	1	7592	0.95	51.1717

Statistics					
Description	Symbol	Avg	Max	Min	Avg/Min
Calc Zone #2	+	1.0 fc	12.7 fc	0.0 fc	N/A

COPYRIGHT 2024 - ALL DRAWINGS ARE AND SHALL REMAIN THE PROPERTY OF VMP ENGINEERING INC. AND MAY NOT BE USED, DUPLICATED OR ALTERED WITHOUT THE WRITTEN CONSENT OF THE ENGINEER.

**VMP ENGINEERING INC.**  
6225 Euclid Parkway  
Dublin, Ohio 43016  
Phone: 614.408.3862  
www.VMPEngineering.com

HARRIS AUTOMOTIVE  
6319 MAXTOWN ROAD  
GENOA TOWNSHIP, OH

DATE: 12/13/2024  
DWN. BY: VMP  
CHK. BY: VMP  
VMP COMM: #24302

ISSUE FOR: X  
OWNER REVIEW: ☐  
PERMIT: ☐  
BID: ☐  
CONSTRUCTION: ☐  
REVISION: ☐  
AS BUILT: ☐

REVISIONS  
REV. NO./DATE: -/-  
REV. NO./DATE: -/-  
REV. NO./DATE: -/-  
REV. NO./DATE: -/-

SHEET NUMBER  
**ES1**  
SITE PHOTOMETRY